

# XLE

## SPECIFICATIONS

MODEL		XLE-46SA20	XLE-58SA30-S	XLE-510SA30-S	XLE-610SA30-S	XLE-612SA30-S
Body:	Length	6' 0"	8' 8"	10' 8"	10' 8"	12' 8"
	Width	4'	5'	5'	6'	6'
	Overall:	Length	9' 6"	11' 6"	13' 6"	13' 6"
	Width	5' 2"	7' 0"	7' 0"	8' 0"	8' 0"
	Height	5' 9"	6' 11"	6' 11"	6' 11"	6' 11"
Interior:	Length	5' 9"	8' 4"	10' 4"	10' 4"	12' 4"
	Width	3' 9"	4' 9"	4' 9"	5' 9"	5' 9"
	Height	3' 11"	5' 4-3/4"	5' 4-3/4"	5' 4-3/4"	5' 4-3/4"
	Platform Height	20"	18"	18"	18"	18"
Axle:	Quantity	1	1	1	1	1
	Capacity	2000	3000	3000	3000	3000
	Type	Straight	4" Drop	4" Drop	4" Drop	4" Drop
	Suspension	Spring	Spring	Spring	Spring	Spring
	Brakes	N/A	N/A	N/A	N/A	N/A
Tire:	Size	12"	15"	15"	15"	15"
	Type	Bias Ply	Radial	Radial	Radial	Radial
	Load Range	'C'	'C'	'C'	'C'	'C'
	Wheel	White Mod	White Mod	White Mod	White Mod	White Mod
	Wheel Bolt Pattern	5 on 4-1/2	5 on 4-1/2	5 on 4-1/2	5 on 4-1/2	5 on 4-1/2
Hitch:	Ball Size	2"	2"	2"	2"	2"
	To Top of Ball	16-1/2"	15-1/2"	15-1/2"	15-1/2"	15-1/2"
Tongue Jack:	Type	Swing-Away	Top-Wind	Top-Wind	Top-Wind	Top-Wind
	Capacity	2000lbs	2000lbs	2000lbs	2000lbs	2000lbs
Weight:	Hitch	10%-15%	10%-15%	10%-15%	10%-15%	10%-15%
	Curb (lbs)	545	800	885	1015	1140
	GVWR (lbs)	2000	2990	2990	2990	2990
	Avg. Payload (lbs)	1455	2190	2065	1975	1850
Rear Door:	Style	Single Door	Single Door	Single Door	Double Door	Double Door
	Width	42"	54"	54"	66"	66"
	Height	41-3/4"	60"	60"	60"	60"
	Lock Style	Bar Lock	Bar Lock	Bar Lock	Cam Bar	Cam Bar
Side Door:	Width	N/A	Optional	Optional	Optional	Optional
	Height	N/A	Optional	Optional	Optional	Optional
	Lock Style	N/A	Optional	Optional	Optional	Optional
	Tube Main Rails	2" x 3"	2" x 3"	2" x 3"	2" x 3"	2" x 3"
	12v End Connector	4-Way	4-Way	4-Way	4-Way	4-Way
	ATP Stoneguard	12" x .025	12" x .025	12" x .025	12" x .025	12" x .025
	Interior Sidewall Liner	5.2mm Lauan	5.2mm Lauan	5.2mm Lauan	5.2mm Lauan	5.2mm Lauan
	Flooring	3/4" Engineered	3/4" Engineered	3/4" Engineered	3/4" Engineered	3/4" Engineered

### STANDARD FEATURES

- 12v LED Dome Light (1)
- 12"H .045 ATP Stoneguard
- Weather Guard Exterior Fasteners
- Top Wind Jack w/ Sand Pad
- Safety Chains
- Spring Suspension Axles (4" Drop)
- E-Z Lube Hubs
- One-Piece Aluminum Roof
- Smooth Aluminum Fenders
- 12v LED Tail/Marker/Clearance Lights
- .030 Prefinished Aluminum Exterior Skin (13 Colors)
- 24" OC Floor Crossmembers
- 24" OC Vertical Posts
- 24" OC Roof Bows
- 1-Year Limited Warranty