

XLV

SPECIFICATIONS

MODEL		XLV-58SA30-S	XLV-510SA30-S	XLV-610SA30-S	XLV-612SA30-S	XLV-614SA30-S	XLV-712SA35-8.5-S	XLV-712TA35-8.5-S	XLV-714SA35-8.5-S	XLV-714TA35-8.5-S	XLV-716TA35-8.5-S
Body:	Length	10' 0"	12' 0"	12' 0"	14' 0"	16' 0"	14' 0"	14' 0"	16' 0"	16' 0"	18' 0"
	Width	5' 0"	5' 0"	6' 0"	6' 0"	6' 0"	7' 0"	7' 0"	7' 0"	7' 0"	7' 0"
	Overall:	Length	11' 9"	13' 9"	13' 9"	15' 9"	17' 9"	15' 11"	15' 11"	15' 11"	15' 11"
	Width	80"	80"	92"	92"	92"	102"	102"	102"	102"	102"
	Height	80"	80"	92"	92"	92"	93"	93"	93"	93"	93"
Interior:	Length	9' 7"	11' 7"	11' 7"	13' 7"	15' 7"	13' 7"	13' 7"	15' 7"	15' 7"	17' 7"
	Width	56"	56"	68"	68"	68"	80"	80"	80"	80"	80"
	Height	61"	61"	73"	73"	73"	73"	73"	73"	73"	73"
	Platform Height	18"	18"	18"	18"	18"	19"	19"	19"	19"	19"
Axle:	Quantity	1	1	1	1	1	1	2	1	2	2
	Capacity	3000	3000	3000	3000	3000	3500	3500	3500	3500	3500
	Type	4" Drop	4" Drop	4" Drop	4" Drop	4" Drop	4" Drop	4" Drop	4" Drop	4" Drop	4" Drop
	Suspension	Spring	Spring	Spring	Spring	Spring	Spring	Spring	Spring	Spring	Spring
	Brakes	N/A	N/A	N/A	N/A	N/A	Electric Drum	Electric Drum	Electric Drum	Electric Drum	Electric Drum
Tire:	Size	15"	15"	15"	15"	15"	15"	15"	15"	15"	15"
	Type	Radial	Radial	Radial	Radial	Radial	Radial	Radial	Radial	Radial	Radial
	Load Range	'C'	'C'	'C'	'C'	'C'	'C'	'C'	'C'	'C'	'C'
	Wheel	White Mod	White Mod	White Mod	White Mod	White Mod	White Mod	White Mod	White Mod	White Mod	White Mod
	Wheel Bolt Pattern	5 on 4-1/2	5 on 4-1/2	5 on 4-1/2	5 on 4-1/2	5 on 4-1/2	5 on 4-1/2	5 on 4-1/2	5 on 4-1/2	5 on 4-1/2	5 on 4-1/2
Hitch:	Ball Size	2"	2"	2"	2"	2"	2"	2-5/16"	2"	2-5/16"	2-5/16"
	To Top of Ball	18"	18"	18"	18"	18"	18"	18"	18"	18"	18"
Tongue Jack:	Type	Top-Wind	Top-Wind	Top-Wind	Top-Wind	Top-Wind	Top-Wind	Top-Wind	Top-Wind	Top-Wind	Top-Wind
	Capacity	2000lbs	2000lbs	2000lbs	2000lbs	2000lbs	2000lbs	2000lbs	2000lbs	2000lbs	2000lbs
Weight:	Hitch	10%-15%	10%-15%	10%-15%	10%-15%	10%-15%	10%-15%	10%-15%	10%-15%	10%-15%	10%-15%
	Curb (lbs)	935	1020	1235	1365	1495	1730	1950	1865	2085	2220
	GVWR (lbs)	2990	2990	2990	2990	2990	3500	7000	3500	7000	7000
	Avg. Payload (lbs)	2055	1970	1755	1625	1495	1770	5050	1635	4915	4780
Rear Door:	Style	Double Door	Double Door	Double Door	Double Door	Double Door	Double Door	Double Door	Double Door	Double Door	Double Door
	Width	52"	52"	64"	64"	64"	76"	76"	76"	76"	76"
	Height	54"	54"	66"	66"	66"	67"	67"	67"	67"	67"
	Lock Style	Cam Bar	Cam Bar	Cam Bar	Cam Bar	Cam Bar	Cam Bar	Cam Bar	Cam Bar	Cam Bar	Cam Bar
Side Door:	Width	Optional	Optional	32"	32"	32"	32"	32"	32"	32"	32"
	Height	Optional	Optional	64"	64"	64"	64"	64"	64"	64"	64"
	Lock Style	N/A	N/A	RV Flush Lock	RV Flush Lock	RV Flush Lock	RV Flush Lock	RV Flush Lock	RV Flush Lock	RV Flush Lock	RV Flush Lock
	Tube Main Rails	2" x 3"	2" x 3"	2" x 3"	2" x 3"	2" x 3"	2" x 4"	2" x 4"	2" x 4"	2" x 4"	2" x 4"
	12v End Connector	4-Way	4-Way	4-Way	4-Way	4-Way	7-Way	7-Way	7-Way	7-Way	7-Way
	ATP Stoneguard	24" x .045	24" x .045	24" x .045	24" x .045	24" x .045	24" x .045	24" x .045	24" x .045	24" x .045	24" x .045
	Interior Sidewall Liner	3/8" Plywood	3/8" Plywood	3/8" Plywood	3/8" Plywood	3/8" Plywood	3/8" Plywood	3/8" Plywood	3/8" Plywood	3/8" Plywood	3/8" Plywood
	Flooring	3/4" Engineered	3/4" Engineered	3/4" Engineered	3/4" Engineered	3/4" Engineered	3/4" Engineered	3/4" Engineered	3/4" Engineered	3/4" Engineered	3/4" Engineered

STANDARD FEATURES

- 12v LED Dome Light w/Switch (1)
- 24"H .045 ATP Stoneguard
- Weather Guard Exterior Fasteners
- Top Wind Jack w/ Sand Pad
- Safety Chains
- Spring Suspension Axle (4" Drop)
- E-Z Lube Hubs
- Fold-Down Rear Stabilizer Jacks
- Flow-Thru Sidewall Vents
- One-Piece Aluminum Roof
- Smooth Aluminum Fenders
- 12v LED Tail/Marker/Clearance Lights
- .030 Prefinished Aluminum Exterior Skin (13 Colors)
- 24" OC Floor Crossmembers
- 24" OC Vertical Posts
- 24" OC Roof Bows
- 1-Year Limited Warranty