

SPECIFICATIONS

UT - 5 Wide

MODEL		UT-58SA30	UT-58SA35	UT-510SA30	UT-510SA35	UT-512SA30	UT-512SA35	UT-512TA35
Body:	Length	8' 9"	8' 9"	10' 9"	10' 9"	12' 9"	12' 9"	12' 9"
	Width	5' 0"	5' 0"	5' 0"	5' 0"	5' 0"	5' 0"	5' 0"
Overall:	Length	12' 0"	12' 0"	14' 0"	14' 0"	16' 0"	16' 0"	16' 0"
	Width	6' 8"	6' 8"	6' 8"	6' 8"	6' 8"	6' 8"	6' 8"
	Height	6' 9"	6' 9"	6' 9"	6' 9"	6' 9"	6' 9"	6' 9"
Interior:	Length	8' 4"	8' 4"	10' 4"	10' 4"	12' 4"	12' 4"	12' 4"
	Width	4' 8"	4' 8"	4' 8"	4' 8"	4' 8"	4' 8"	4' 8"
	Height	5' 1"	5' 1"	5' 1"	5' 1"	5' 1"	5' 1"	5' 1"
Rear Door Opening:	Width	4' 4"	4' 4"	4' 4"	4' 4"	4' 4"	4' 4"	4' 4"
	Height	4' 7"	4' 7"	4' 7"	4' 7"	4' 7"	4' 7"	4' 7"
Platform Height		17-3/4"	17-3/4"	17-3/4"	17-3/4"	17-3/4"	17-3/4"	17-3/4"
Axles		1	1	1	1	1	1	2
Axle Type		4" Drop	4" Drop	4" Drop	4" Drop	4" Drop	4" Drop	4" Drop
Suspension		Spring or Torsion	Spring or Torsion	Spring or Torsion	Spring or Torsion	Spring or Torsion	Spring or Torsion	Spring or Torsion
Tire Size		ST205/75R15	ST205/75R15	ST205/75R15	ST205/75R15	ST205/75R15	ST205/75R15	ST205/75R15
Load Range		C	C	C	C	C	C	C
Wheel Bolt Pattern		5-Bolt/4.5	5-Bolt/4.5	5-Bolt/4.5	5-Bolt/4.5	5-Bolt/4.5	5-Bolt/4.5	5-Bolt/4.5
Hitch Ball Size		2"	2"	2"	2"	2"	2"	2 5/16"
Hitch to Top of Ball		16"	16"	16"	16"	16"	16"	16"
Hitch Weight (% of Curb Weight)		10-15%	10-15%	10-15%	10-15%	10-15%	10-15%	10-15%
Avg Curb Weight (lbs.)		880	900	980	1000	1200	1220	1600
GVWR (lbs.)		2,990	3,500	2,990	3,500	2,990	3,500	7,000
GAWR (lbs.)		3,000	3,500	3,000	3,500	3,000	3,500	7,000
Avg. Payload Capacity		2110	2600	2010	2500	1790	2280	5400

Specifications and features subject to change without notice.