

SPECIFICATIONS

UT - 6 Wide 3500lb Axles

MODEL		UT-610SA30	UT-610SA35	UT-612SA30	UT-612SA35	UT-614SA30	UT-614SA35	UT-612TA35	UT-614TA35
Body:	Length	10' 9"	10' 9"	12' 9"	12' 9"	14' 9"	14' 9"	12' 9"	14' 9"
	Width	6' 0"	6' 0"	6' 0"	6' 0"	6' 0"	6' 0"	6' 0"	6' 0"
Overall:	Length	14' 0"	14' 0"	16' 0"	16' 0"	18' 0"	18' 0"	16' 0"	18' 0"
	Width	7' 8"	7' 8"	7' 8"	7' 8"	7' 8"	7' 8"	7' 8"	7' 8"
	Height	7' 9"	7' 9"	7' 9"	7' 9"	7' 9"	7' 9"	7' 9"	7' 9"
Interior:	Length	10' 4"	10' 4"	12' 4"	12' 4"	14' 4"	14' 4"	12' 4"	14' 4"
	Width	5' 8"	5' 8"	5' 8"	5' 8"	5' 8"	5' 8"	5' 8"	5' 8"
	Height	6' 1"	6' 1"	6' 1"	6' 1"	6' 1"	6' 1"	6' 1"	6' 1"
Rear Door Opening:	Width	5' 4"	5' 4"	5' 4"	5' 4"	5' 4"	5' 4"	5' 4"	5' 4"
	Height	5' 7"	5' 7"	5' 7"	5' 7"	5' 7"	5' 7"	5' 7"	5' 7"
Platform Height		17-3/4"	17-3/4"	17-3/4"	17-3/4"	17-3/4"	17-3/4"	17-3/4"	17-3/4"
Axles		1	1	1	1	1	1	2	2
Axle Type		4" Drop	4" Drop	4" Drop	4" Drop	4" Drop	4" Drop	4" Drop	4" Drop
Suspension		Spring or Torsion	Spring or Torsion	Spring or Torsion	Spring or Torsion	Spring or Torsion	Spring or Torsion	Spring or Torsion	Spring or Torsion
Tire Size		ST205/75R15	ST205/75R15	ST205/75R15	ST205/75R15	ST205/75R15	ST205/75R15	ST205/75R15	ST205/75R15
Load Range		C	C	C	C	C	C	C	C
Wheel Bolt Pattern		5-Bolt/4.5	5-Bolt/4.5	5-Bolt/4.5	5-Bolt/4.5	5-Bolt/4.5	5-Bolt/4.5	5-Bolt/4.5	5-Bolt/4.5
Hitch Ball Size		2"	2"	2"	2"	2"	2"	2-5/16"	2-5/16"
Hitch to Top of Ball		16"	16"	16"	16"	16"	16"	16"	16"
Hitch Weight (% of Curb Weight)		10-15%	10-15%	10-15%	10-15%	10-15%	10-15%	10-15%	10-15%
Avg Curb Weight (lbs.)		1200	1220	1320	1340	1410	1430	1600	1900
GVWR (lbs.)		2,990	3,500	2,990	3,500	2,990	3,500	7,000	7,000
GAWR (lbs.)		3,000	3,500	3,000	3,500	3,000	3,500	7,000	7,000
Avg. Payload Capacity		1790	2280	1670	2160	1580	2070	5400	5100

Specifications and features subject to change without notice.