

SPECIFICATIONS

UT - 6 Wide 5000lb Spring & 5200lb Torsion Axles

		UT-610SA50	UT-610SA52	UT-612SA50	UT-612SA52	UT-614SA50	UT-614SA52	UT-612TA50	UT-612TA52	UT-614TA50	UT-614TA52
MODEL											
Body:	Length	10' 9"	10' 9"	12' 9"	12' 9"	14' 9"	14' 9"	12' 9"	12' 9"	14' 9"	14' 9"
	Width	6' 0"	6' 0"	6' 0"	6' 0"	6' 0"	6' 0"	6' 0"	6' 0"	6' 0"	6' 0"
Overall:	Length	14' 0"	14' 0"	16' 0"	16' 0"	18' 0"	18' 0"	16' 0"	16' 0"	18' 0"	18' 0"
	Width	7' 8"	7' 8"	7' 8"	7' 8"	7' 8"	7' 8"	7' 8"	7' 8"	7' 8"	7' 8"
	Height	7' 9"	7' 9"	7' 9"	7' 9"	7' 9"	7' 9"	7' 9"	7' 9"	7' 9"	7' 9"
Interior:	Length	10' 4"	10' 4"	12' 4"	12' 4"	14' 4"	14' 4"	12' 4"	12' 4"	14' 4"	14' 4"
	Width	5' 8"	5' 8"	5' 8"	5' 8"	5' 8"	5' 8"	5' 8"	5' 8"	5' 8"	5' 8"
	Height	6' 1"	6' 1"	6' 1"	6' 1"	6' 1"	6' 1"	6' 1"	6' 1"	6' 1"	6' 1"
Rear Door Opening:	Width	5' 4"	5' 4"	5' 4"	5' 4"	5' 4"	5' 4"	5' 4"	5' 4"	5' 4"	5' 4"
	Height	5' 7"	5' 7"	5' 7"	5' 7"	5' 7"	5' 7"	5' 7"	5' 7"	5' 7"	5' 7"
Platform Height		17-3/4"	17-3/4"	17-3/4"	17-3/4"	17-3/4"	17-3/4"	17-3/4"	17-3/4"	17-3/4"	17-3/4"
Axles		1	1	1	1	1	1	2	2	2	2
Axle Type		4" Drop	4" Drop	4" Drop	4" Drop	4" Drop	4" Drop	4" Drop	4" Drop	4" Drop	4" Drop
Suspension		Spring	Torsion	Spring	Torsion	Spring	Torsion	Spring	Torsion	Spring	Torsion
Tire Size		ST225/75R15	ST225/75R15	ST225/75R15	ST225/75R15	ST225/75R15	ST225/75R15	ST225/75R15	ST225/75R15	ST225/75R15	ST225/75R15
Load Range		E	E	E	E	E	E	E	E	E	E
Wheel Bolt Pattern		6-Bolt/5.5	6-Bolt/5.5	6-Bolt/5.5	6-Bolt/5.5	6-Bolt/5.5	6-Bolt/5.5	6-Bolt/5.5	6-Bolt/5.5	6-Bolt/5.5	6-Bolt/5.5
Hitch Ball Size		2-5/16"	2-5/16"	2-5/16"	2-5/16"	2-5/16"	2-5/16"	2-5/16"	2-5/16"	2-5/16"	2-5/16"
Hitch to Top of Ball		16"	16"	16"	16"	16"	16"	16"	16"	16"	16"
Hitch Weight (% of Curb Weight)		10-15%	10-15%	10-15%	10-15%	10-15%	10-15%	10-15%	10-15%	10-15%	10-15%
Avg Curb Weight (lbs.)		1420	1420	1620	1620	1840	1840	1900	1900	2200	2200
GVWR (lbs.)		5000	5200	5000	5200	5000	5200	9800	9900	9800	9900
GAWR (lbs.)		5000	5200	5000	5200	5000	5200	10000	10200	10000	10200
Avg. Payload Capacity		3580	3780	3380	3580	3160	3360	7900	8000	7600	7700

Specifications and features subject to change without notice.